

VEINVIEWER® Flex

CONTROL PANEL:

FUNCTIONS AND MODES Power button hold for 1s to switch on Function button 1* adjust the image to one of 3 sizes Status indicator: Green: Powered on Function button 2* Red: Battery level < 25% MaxBright and CathCompass™ Red flashing: Battery level < 10% Orange: System notice Capture a (see icons on image border or troubletime-stamped image shooting in IFU) Flash Orange: Invalid button press Image mode button* 4 view options



*Continue pressing to scroll through options.

VEINVIEWER® Flex

VEINVISUALIZATION IN A NEW LIGHT.

DETAILED FUNCTION DESCRIPTION



Resize (3 sizes available)










F2: MaxBright and CathCompass™

Max Bright (maximum brightness image)



Helpful for use in environments with higher ambient light levels, such as sunlight.


CathCompass™



Enable or disable the catheter sizing reference graphic from the display.




Image Mode (4 options)




Universal mode appropriate for all patients



Fine detail mode for pediatrics, neonates, or sclerotherapy patients



Universal mode inverted



Fine detail mode inverted

0

Photo

Capture a timestamped image of the vein conditions by pressing the camera function button. A camera symbol appears in the border to indicate a saved image, which can be transferred as PNG file to computer via the USB connection.

CORRECT FOCUSSING



Correct focus position is indicated by the text in the image being clearly legible:

